


## FEATURES

- ESD Protection for RS-232 Bus Pins
  - $\pm 15$ -kV Human-Body Model (HBM)
- Meets or Exceeds the Requirements of TIA/EIA-232-F and ITU v.28 Standards
- Operates at 5-V  $V_{CC}$  Supply
- Four Drivers and Five Receivers
- Operates up to 120 kbit/s
- Low Supply Current in Shutdown Mode . . . 15  $\mu$ A Typ
- External Capacitors . . .  $4 \times 0.1$  F
- Designed to Be Interchangeable With Industry Standard '213 Devices
- Latch-Up Performance Exceeds 100 mA Per JESD 78, Class II

DB, DW, OR PW PACKAGE  
(TOP VIEW)



## APPLICATIONS

- Battery-Powered Systems
- PDAs
- Notebooks
- Laptops
- Palmtop PCs
- Hand-Held Equipment

## DESCRIPTION/ ORDER INFORMATION

The TRS213 device consists of four line drivers, five line receivers, and a dual charge-pump circuit with  $\pm 15$ -kV ESD protection pin to pin (serial-port connection pins, including GND). The device meets the requirements of TIA/EIA-232-F and provides the electrical interface between an asynchronous communication controller and the serial-port connector. The charge pump and four small external capacitors allow operation from a single 5-V supply. The devices operate at data signaling rates up to 120 kbit/s and a maximum of 30-V/ $\mu$ s driver output slew rate.

The TRS213 has an active-low shutdown ( $\overline{\text{SHDN}}$ ) and an active-high enable control (EN). In shutdown mode, the charge pumps are turned off, V+ is pulled down to  $V_{CC}$ , V- is pulled to GND, and the transmitter outputs are disabled. This reduces supply current typically to 1  $\mu$ A. Two receivers of the TRS213 are active during shutdown.



Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

**TRS213**  
**5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER**  
**WITH ±15-kV ESD PROTECTION**

SLLS807–JUNE 2007

**ORDERING INFORMATION**

| T <sub>A</sub> | PACKAGE <sup>(1)(2)</sup> |               | ORDERABLE PART NUMBER | TOP-SIDE MARKING |
|----------------|---------------------------|---------------|-----------------------|------------------|
| 0°C to 70°C    | SOIC – DW                 | Tube of 20    | TRS213CDW             | TRS213C          |
|                |                           | Reel of 1000  | TRS213CDWR            |                  |
|                | SSOP – DB                 | Tube of 50    | TRS213CDB             | TRS213C          |
|                |                           | Reel of 2000  | TRS213CDBR            |                  |
| TSSOP – PW     | Tape and reel             | TRS213CPWR    | TRS213C               |                  |
| –40°C to 85°C  | SOIC – DW                 | Tube of 20    | TRS213IDW             | TRS213I          |
|                |                           | Reel of 1000  | TRS213IDWR            |                  |
|                | SSOP – DB                 | Tube of 50    | TRS213IDB             | TRS213I          |
|                |                           | Reel of 2000  | TRS213IDBR            |                  |
|                | TSSOP – PW                | Tape and reel | TRS213IPWR            | TRS213I          |


- (1) Package drawings, standard packing quantities, thermal data, symbolization, and PCB design guidelines are available at [www.ti.com/sc/package](http://www.ti.com/sc/package).
- (2) For the most current package and ordering information, see the Package Option Addendum at the end of this document, or see the TI website at [www.ti.com](http://www.ti.com).

**FUNCTION TABLE**

| INPUTS                   |    | DRIVER<br>D1–D4 | RECEIVER |                       | DEVICE STATUS    |
|--------------------------|----|-----------------|----------|-----------------------|------------------|
| $\overline{\text{SHDN}}$ | EN |                 | R1–R3    | R4–R5                 |                  |
| L                        | L  | Z               | Z        | Z                     | Shutdown         |
| L                        | H  | Z               | Z        | Active <sup>(1)</sup> | Shutdown         |
| H                        | L  | All active      | Z        | Z                     | Normal operation |
| H                        | H  | All active      | Active   | Active                | Normal operation |

- (1) See the V<sub>IT+</sub> and V<sub>IT-</sub> change in the Electrical Characteristics table.

**LOGIC DIAGRAM (POSITIVE LOGIC)**



# TRS213

## 5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER WITH $\pm 15$ -kV ESD PROTECTION

SLLS807–JUNE 2007

### Absolute Maximum Ratings<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

|                  |   | MIN                   | MAX      | UNIT |
|------------------|---|-----------------------|----------|------|
| V <sub>CC</sub>  | Supply voltage range                              | –0.3                  | 6        | V    |
| V+               | Positive charge-pump voltage range <sup>(2)</sup> | V <sub>CC</sub> – 0.3 | 14       | V    |
| V–               | Negative charge-pump voltage range <sup>(2)</sup> | 0.3                   | –14      | V    |
| V <sub>I</sub>   | Input voltage range                               | Drivers               | V+ + 0.3 | V    |
|                  |   | Receivers             | ±30      |      |
| V <sub>O</sub>   | Output voltage range                              | Drivers               | V– – 0.3 | V    |
|                  |   | Receivers             | –0.3     |      |
| DO <sub>UT</sub> | Short-circuit duration                            | Continuous            |          |      |
| θ <sub>JA</sub>  | Package thermal impedance <sup>(3)(4)</sup>       | DB package            | 62       | C°/W |
|                  |   | DW package            | 46       |      |
|                  |   | PW package            |          |      |
| T <sub>J</sub>   | Operating virtual junction temperature            |                       | 150      | C°   |
| T <sub>stg</sub> | Storage temperature range                         | –65                   | 150      | C°   |

(1) Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

(2) All voltages are with respect to network GND.

(3) Maximum power dissipation is a function of T<sub>J</sub>(max), θ<sub>JA</sub>, and T<sub>A</sub>. The maximum allowable power dissipation at any allowable ambient temperature is P<sub>D</sub> = (T<sub>J</sub>(max) – T<sub>A</sub>)/θ<sub>JA</sub>. Operating at the absolute maximum T<sub>J</sub> of 150°C can affect reliability.

(4) The package thermal impedance is calculated in accordance with JESD 51-7.

### Recommended Operating Conditions<sup>(1)</sup>

See [Figure 4](#)

|                 |  | MIN     | NOM | MAX | UNIT |
|-----------------|--|---------|-----|-----|------|
| Supply voltage  |  | 4.5     | 5   | 5.5 | V    |
| V <sub>IH</sub> | Driver high-level input voltage            | 2       |     |     | V    |
|                 | Control high-level input voltage           | 2.4     |     |     |      |
| V <sub>IL</sub> | Driver and control low-level input voltage |         |     | 0.8 | V    |
| V <sub>I</sub>  | Driver and control input voltage           | 0       |     | 5.5 | V    |
|                 | Receiver input voltage                     | –30     |     | 30  |      |
| T <sub>A</sub>  | Operating free-air temperature             | TRS213C | 0   | 70  | °C   |
|                 |  | TRS213I | –40 | 85  |      |

(1) Test conditions are C1–C4 = 0.1 μF at V<sub>CC</sub> = 5 V ± 0.5 V.

### Electrical Characteristics<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

| PARAMETER         | TEST CONDITIONS  | MIN | TYP <sup>(2)</sup> | MAX | UNIT |
|-------------------|--|-----|--------------------|-----|------|
| I <sub>CC</sub>   | Supply current<br>No load, See <a href="#">Figure 6</a>                        |     | 14                 | 20  | mA   |
| I <sub>SHDN</sub> | Shutdown supply current<br>T <sub>A</sub> = 25°C, See <a href="#">Figure 1</a> |     | 15                 | 50  | μA   |

(1) Test conditions are C1–C4 = 0.1 μF at V<sub>CC</sub> = 5 V ± 0.5 V.

(2) All typical values are at V<sub>CC</sub> = 5 V, and T<sub>A</sub> = 25°C.

## DRIVER SECTION

### Electrical Characteristics<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted) (see Figure 4)

| PARAMETER                      |                                  | TEST CONDITIONS  | MIN | TYP <sup>(2)</sup> | MAX      | UNIT     |
|--------------------------------|----------------------------------|--|-----|--------------------|----------|----------|
| V <sub>OH</sub>                | High-level output voltage        | DOOUT at R <sub>L</sub> = 3 k $\Omega$ to GND                  | 5   | 9                  |          | V        |
| V <sub>OL</sub>                | Low-level output voltage         | DOOUT at R <sub>L</sub> = 3 k $\Omega$ to GND                  | –5  | –9                 |          | V        |
| I <sub>IH</sub>                | Control high-level input current | EN, $\overline{\text{SHDN}}$ = 5 V                             |     | 3                  | 10       | $\mu$ A  |
| I <sub>IL</sub>                | Driver low-level input current   | DIN = 0 V  |     | –15                | –200     | $\mu$ A  |
|                                | Control low-level input current  | EN, $\overline{\text{SHDN}}$ = 0 V                             |     | –3                 | –10      |          |
| I <sub>OS</sub> <sup>(3)</sup> | Short-circuit output current     | V <sub>CC</sub> = 5.5 V, V <sub>O</sub> = 0 V                  |     | $\pm 10$           | $\pm 60$ | mA       |
| r <sub>o</sub>                 | Output resistance                | V <sub>CC</sub> , V+, and V– = 0 V, V <sub>O</sub> = $\pm 2$ V | 300 |                    |          | $\Omega$ |

(1) Test conditions are C1–C4 = 0.1  $\mu$ F at V<sub>CC</sub> = 5 V  $\pm$  0.5 V

(2) All typical values are at V<sub>CC</sub> = 5 V, and T<sub>A</sub> = 25°C.

(3) Short-circuit durations should be controlled to prevent exceeding the device absolute power dissipation ratings, and not more than one output should be shorted at a time.

### Switching Characteristics<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

| PARAMETER           |   | TEST CONDITIONS  | MIN | TYP <sup>(2)</sup> | MAX | UNIT       |
|---------------------|---|--|-----|--------------------|-----|------------|
|                     | Maximum data rate                                 | C <sub>L</sub> = 50 pF to 1000 pF, One DOOUT switching, R <sub>L</sub> = 3 k $\Omega$ to 7 k $\Omega$ , See Figure 3 | 120 |                    |     | kbit/s     |
| t <sub>PLH(D)</sub> | Propagation delay time, low- to high-level output | C <sub>L</sub> = 2500 pF, All drivers loaded, R <sub>L</sub> = 3 k $\Omega$ , See Figure 3                           |     | 2                  |     | $\mu$ s    |
| t <sub>PHL(D)</sub> | Propagation delay time, high- to low-level output | C <sub>L</sub> = 2500 pF, All drivers loaded, R <sub>L</sub> = 3 k $\Omega$ , See Figure 3                           |     | 2                  |     | $\mu$ s    |
| t <sub>sk(p)</sub>  | Pulse skew <sup>(3)</sup>                         | C <sub>L</sub> = 150 pF to 2500 pF, See Figure 3, R <sub>L</sub> = 3 k $\Omega$ to 7 k $\Omega$                      |     | 300                |     | ns         |
| SR(tr)              | Slew rate, transition region (see Figure 2)       | C <sub>L</sub> = 50 pF to 1000 pF, V <sub>CC</sub> = 5 V, R <sub>L</sub> = 3 k $\Omega$ to 7 k $\Omega$              | 3   | 6                  | 30  | V/ $\mu$ s |

(1) Test conditions are C1–C4 = 0.1  $\mu$ F at V<sub>CC</sub> = 5 V  $\pm$  0.5 V.

(2) All typical values are at V<sub>CC</sub> = 5 V, and T<sub>A</sub> = 25°C.

(3) Pulse skew is defined as (t<sub>PLH</sub> – t<sub>PHL</sub>) of each channel of the same device.

### ESD Protection

over operating free-air temperature range (unless otherwise noted)

| PIN   | TEST CONDITIONS  | TYP      | UNIT |
|-------|------------------|----------|------|
| DOOUT | Human-Body Model | $\pm 15$ | kV   |

# TRS213

## 5-V MULTICHANNEL RS-232 LINE DRIVER/RECEIVER WITH $\pm 15$ -kV ESD PROTECTION

SLLS807–JUNE 2007

### RECEIVER SECTION

#### Electrical Characteristics<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted) (see [Figure 6](#))

| PARAMETER                       |   | TEST CONDITIONS                              |                       | MIN                   | TYP <sup>(2)</sup> | MAX | UNIT |    |
|---------------------------------|---|--|-----------------------|-----------------------|--------------------|-----|------|----|
| V <sub>OH</sub>                 | High-level output voltage                               | I <sub>OH</sub> = -1 mA                      |                       | V <sub>CC</sub> - 0.4 |                    |     | V    |    |
| V <sub>OL</sub>                 | Low-level output voltage                                | I <sub>OH</sub> = 1.6 mA                     |                       | 0.4                   |                    |     | V    |    |
| V <sub>IT+</sub>                | Positive-going input threshold voltage                  | V <sub>CC</sub> = 5 V, T <sub>A</sub> = 25°C | Active mode           | 1.7                   |                    | 2.4 | V    |    |
|                                 |   |  | Shutdown mode (R4–R5) | 1.5                   |                    | 2.4 |      |    |
| V <sub>IT-</sub>                | Negative-going input threshold voltage                  | V <sub>CC</sub> = 5 V, T <sub>A</sub> = 25°C | Active mode           | 0.8                   |                    | 1.2 | V    |    |
|                                 |   |  | Shutdown mode (R4–R5) | 0.6                   |                    | 1.5 |      |    |
| V <sub>hys</sub> <sup>(3)</sup> | Input hysteresis (V <sub>IT+</sub> , V <sub>IT-</sub> ) | V <sub>CC</sub> = 5 V                        |                       | 0.5                   |                    | 1   | V    |    |
| r <sub>I</sub>                  | Input resistance  | V <sub>CC</sub> = 5 V, T <sub>A</sub> = 25°C |                       | 3                     |                    | 5   | 7    | kΩ |
| Output leakage current          |   | EN = 0 V, 0 ≤ ROUT ≤ V <sub>CC</sub> , R1–R3 |                       | ±0.05                 |                    | ±10 | μA   |    |

(1) Test conditions are C1–C4 = 0.1 μF at V<sub>CC</sub> = 5 V ± 0.5 V.

(2) All typical values are at V<sub>CC</sub> = 5 V, and T<sub>A</sub> = 25°C.

(3) No hysteresis in shutdown mode

#### Switching Characteristics<sup>(1)</sup>

over operating free-air temperature range (unless otherwise noted)

| PARAMETER           |   | TEST CONDITIONS                                       |                        | MIN | TYP <sup>(2)</sup> | MAX | UNIT |
|---------------------|---|---|------------------------|-----|--------------------|-----|------|
| t <sub>PLH(R)</sub> | Propagation delay time, low- to high-level output | C <sub>L</sub> = 150 pF, See <a href="#">Figure 4</a> | SHDN = V <sub>CC</sub> | 0.5 |                    | 10  | μs   |
|                     |   |   | SHDN = 0 V, R4–R5      | 4   |                    | 40  |      |
| t <sub>PHL(R)</sub> | Propagation delay time, high- to low-level output | C <sub>L</sub> = 150 pF, See <a href="#">Figure 4</a> |                        | 0.5 |                    | 10  | μs   |
| t <sub>en</sub>     | Output enable time                                | C <sub>L</sub> = 150 pF, See <a href="#">Figure 5</a> |                        | 600 |                    |     | ns   |
| t <sub>dis</sub>    | Output disable time                               | C <sub>L</sub> = 150 pF, See <a href="#">Figure 5</a> |                        | 200 |                    |     | ns   |

(1) Test conditions are C1–C4 = 0.1 μF at V<sub>CC</sub> = 5 V ± 0.5 V.


(2) All typical values are at V<sub>CC</sub> = 5 V, and T<sub>A</sub> = 25°C.

#### ESD Protection


over operating free-air temperature range (unless otherwise noted)

| PIN | TEST CONDITIONS  | TYP | UNIT |
|-----|------------------|-----|------|
| RIN | Human-Body Model | ±15 | kV   |

**PARAMETER MEASUREMENT INFORMATION**




**Figure 1. Shutdown Current Test Circuit**




NOTES: A.  $C_L$  includes probe and jig capacitance.  
B. The pulse generator has the following characteristics:  $Z_O = 50\ \Omega$ , 50% duty cycle,  $t_r \leq 10\text{ ns}$ ,  $t_f \leq 10\text{ ns}$ .

Figure 2. Driver Slew Rate



NOTES: A.  $C_L$  includes probe and jig capacitance.  
B. The pulse generator has the following characteristics:  $Z_O = 50\ \Omega$ , 50% duty cycle,  $t_r \leq 10\text{ ns}$ ,  $t_f \leq 10\text{ ns}$ .


Figure 3. Driver Pulse Skew and Propagation Delay Times



NOTES: A.  $C_L$  includes probe and jig capacitance.  
B. The pulse generator has the following characteristics:  $Z_O = 50\ \Omega$ , 50% duty cycle,  $t_r \leq 10\text{ ns}$ ,  $t_f \leq 10\text{ ns}$ .

Figure 4. Receiver Propagation Delay Times






- NOTES:
- A.  $C_L$  includes probe and jig capacitance.
  - B. The pulse generator has the following characteristics:  $Z_O = 50 \Omega$ , 50% duty cycle,  $t_r \leq 10$  ns,  $t_f \leq 10$  ns.
  - C.  $t_{PLZ}$  and  $t_{PHZ}$  are the same as  $t_{dis}$ .
  - D.  $t_{PZL}$  and  $t_{PZH}$  are the same as  $t_{en}$ .

Figure 5. Receiver Enable and Disable Times

APPLICATION INFORMATION



(1) C3 can be connected to  $V_{CC}$  or GND.

NOTES: A. Resistor values shown are nominal.

B. Nonpolarized ceramic capacitors are acceptable. If polarized tantalum or electrolytic capacitors are used, they should be connected as shown.

Figure 6. Typical Operating Circuit and Capacitor Values

**PACKAGING INFORMATION**

| Orderable Device | Status<br>(1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan<br>(2) | Lead finish/<br>Ball material<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|-----------------|------|-------------|-----------------|--------------------------------------|----------------------|--------------|-------------------------|-------------------------|
| TRS213CDBR       | ACTIVE        | SSOP         | DB              | 28   | 2000        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | 0 to 70      | TRS213C                 | <a href="#">Samples</a> |
| TRS213IDB        | ACTIVE        | SSOP         | DB              | 28   | 50          | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | TRS213I                 | <a href="#">Samples</a> |
| TRS213IDBR       | ACTIVE        | SSOP         | DB              | 28   | 2000        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | TRS213I                 | <a href="#">Samples</a> |
| TRS213IDWR       | ACTIVE        | SOIC         | DW              | 28   | 1000        | RoHS & Green    | NIPDAU                               | Level-1-260C-UNLIM   | -40 to 85    | TRS213I                 | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSELETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "-" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead finish/Ball material - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead finish/Ball material values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:**The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and

continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**

**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**


\*All dimensions are nominal

| Device     | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| TRS213CDBR | SSOP         | DB              | 28   | 2000 | 330.0              | 16.4               | 8.2     | 10.5    | 2.5     | 12.0    | 16.0   | Q1            |
| TRS213IDBR | SSOP         | DB              | 28   | 2000 | 330.0              | 16.4               | 8.2     | 10.5    | 2.5     | 12.0    | 16.0   | Q1            |
| TRS213IDWR | SOIC         | DW              | 28   | 1000 | 330.0              | 32.4               | 11.35   | 18.67   | 3.1     | 16.0    | 32.0   | Q1            |

## TAPE AND REEL BOX DIMENSIONS



\*All dimensions are nominal

| Device     | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|------------|--------------|-----------------|------|------|-------------|------------|-------------|
| TRS213CDBR | SSOP         | DB              | 28   | 2000 | 356.0       | 356.0      | 35.0        |
| TRS213IDBR | SSOP         | DB              | 28   | 2000 | 356.0       | 356.0      | 35.0        |
| TRS213IDWR | SOIC         | DW              | 28   | 1000 | 350.0       | 350.0      | 66.0        |


**TUBE**


\*All dimensions are nominal

| Device    | Package Name | Package Type | Pins | SPQ | L (mm) | W (mm) | T (μm) | B (mm) |
|-----------|--------------|--------------|------|-----|--------|--------|--------|--------|
| TRS213IDB | DB           | SSOP         | 28   | 50  | 530    | 10.5   | 4000   | 4.1    |

DW (R-PDSO-G28)

PLASTIC SMALL OUTLINE



4040000-6/G 01/11

- NOTES:
- All linear dimensions are in inches (millimeters). Dimensioning and tolerancing per ASME Y14.5M-1994.
  - This drawing is subject to change without notice.
  - Body dimensions do not include mold flash or protrusion not to exceed 0.006 (0,15).
  - Falls within JEDEC MS-013 variation AE.




# DB0028A



# PACKAGE OUTLINE

## SSOP - 2 mm max height

SMALL OUTLINE PACKAGE



4214853/B 03/2018

### NOTES:


1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.
4. This dimension does not include interlead flash. Interlead flash shall not exceed 0.25 mm per side.
5. Reference JEDEC registration MO-150.

# EXAMPLE BOARD LAYOUT


DB0028A

SSOP - 2 mm max height

SMALL OUTLINE PACKAGE



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE: 10X



4214853/B 03/2018

NOTES: (continued)


- 6. Publication IPC-7351 may have alternate designs.
- 7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

DB0028A

SSOP - 2 mm max height

SMALL OUTLINE PACKAGE



NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2022, Texas Instruments Incorporated